



SPECIFICATION SHEET

Sloped Recessed Dimmable LED Downlight

Item Number **50840**


Specifications

Energy Used (Watts).....	13
Incandescent Equivalent Wattage	80
Domestic Code	13R/6"/LED/DIM/SLP/FL/27
Volts	120
Baffle.....	Step
Brightness (Lumens)	900
Average Rated Hours.....	35,000
Life (in years)*.....	31.9
Light Appearance (Kelvin).....	2700
Beam Spread	98°
Beam Type.....	Flood
CRI	90
Efficacy (LPW).....	69
Number of LED Modules.....	21
Dimming Range.....	10% - 100%
Estimated Yearly Energy Cost**.....	\$1.57
Package Type	Box
Gimbal ring allows the downlight to rotate 355°.	
Gimbal ring allows the downlight to slope up to 45° in either direction.	



Physical Characteristics

Color Designation.....	Warm White
Finish.....	Frost
Housing Material.....	Aluminum
Base.....	Medium
MOL	3.5"
MOD	7.28"



Limited Warranty

This luminaire is warranted to be free from defects in material and workmanship for 5 years (based on using 3 hours per day).

Warning

- Turn power off before inspection, installation, or removal.
- Risk of electric shock - Do not use where exposed to water or weather.
- Suitable for Damp Locations.
- Do not open – no user serviceable parts inside.
- This device is not intended for use with emergency exit luminaires or emergency exit lights.
- This device complies with Part 15 of the FCC rules and has been tested and found to comply with the limits for a Class B digital device. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. Any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment.
- This luminaire may not be compatible with all dimmers.

*Based on 3 hrs./day

**Based on 3 hrs./day 11¢/kWh - Cost depends on rates and use.

Recessed LED Downlight Dimmer Compatibility

Brand	Model
AH	SDM/600/WHTTE, SDM3/1000/WHITE
CTL	DM600-12-3
GE	18024
General Protecht	LUXDM600-12
Leviton	6683, 603-6631-A, 6631-A, 6631-LA, 6683-10Z, IPI06-1LZ, IPI10-1LZ, NO.6672 LIGHT ALMOND, NO.IPLO6 WHITE
Lutron	S-603PH-WH

Specifications are subject to change without notice, please visit www.westinghouselighting.com for latest information.

Call 1-800-999-2226 or visit www.westinghouselighting.com.

©, WESTINGHOUSE, and INNOVATION YOU CAN BE SURE OF are trademarks of Westinghouse Electric Corporation.
Used under license by Westinghouse Lighting. All Rights Reserved.